

Extruded Acrylic Tube

Outer Dia. (mm)	Inner Dia. (mm)	Thickness (mm)	Outer Dia. Tolerance	Length (mm)
5	3	1	± 0.15	2000
6	4	1	± 0.15	2000
7	5	1	± 0.15	2000
8	6	1	± 0.15	2000
8	5	1.5	± 0.15	2000
10	8	1	± 0.20	2000
10	7	1.5	± 0.20	2000
10	6	2	± 0.20	2000
12	10	1	± 0.20	2000
12	8	2	± 0.20	2000
12	6	3	± 0.20	2000
13	9	2	± 0.20	2000
13	7	3	± 0.20	2000
14	10	2	± 0.20	2000
14	8	3	± 0.20	2000
15	13	1	± 0.20	2000
15	11	2	± 0.20	2000
15	9	3	± 0.20	2000
16	12	2	± 0.30	2000
16	10	3	± 0.30	2000
18	14	2	± 0.30	2000
18	12	3	± 0.30	2000
20	18	1	± 0.30	2000
20	16	2	± 0.30	2000
20	14	3	± 0.30	2000
22	18	2	± 0.30	2000

22	16	3	± 0.30	2000
25	21	2	± 0.40	2000
25	19	3	± 0.40	2000
28	24	2	± 0.40	2000
28	22	3	± 0.40	2000
30	26	2	± 0.40	2000
30	24	3	± 0.40	2000
30	22	4	± 0.40	2000
30	20	5	± 0.40	2000
32	28	2	± 0.40	2000
32	26	3	± 0.40	2000
32	24	4	± 0.40	2000
35	31	2	± 0.40	2000
35	29	3	± 0.40	2000
38	34	2	± 0.40	2000
38	32	3	± 0.40	2000
38	30	4	± 0.40	2000
38	28	5	± 0.40	2000
40	36	2	± 0.40	2000
40	34	3	± 0.40	2000
40	32	4	± 0.40	2000
40	30	5	± 0.40	2000
45	41	2	± 0.40	2000
45	39	3	± 0.40	2000
45	37	4	± 0.40	2000
45	35	5	± 0.40	2000
50	46	2	± 0.40	2000
50	44	3	± 0.40	2000
50	42	4	± 0.40	2000
50	40	5	± 0.40	2000
60	56	2	± 0.40	2000
60	54	3	± 0.40	2000

60	52	4	± 0.40	2000
60	50	5	± 0.40	2000
70	66	2	± 0.60	2000
70	64	3	± 0.60	2000
70	62	4	± 0.60	2000
70	60	5	± 0.60	2000
80	76	2	± 0.60	2000
80	74	3	± 0.60	2000
80	72	4	± 0.60	2000
80	70	5	± 0.60	2000
90	86	2	± 0.60	2000
90	84	3	± 0.60	2000
90	82	4	± 0.60	2000
90	80	5	± 0.60	2000
100	96	2	± 0.80	2000
100	94	3	± 0.80	2000
100	92	4	± 0.80	2000
100	90	5	± 0.80	2000
110	104	3	± 1.00	2000
110	102	4	± 1.00	2000
110	100	5	± 1.00	2000
120	114	3	± 1.00	2000
120	112	4	± 1.00	2000
120	110	5	± 1.00	2000
125	119	3	± 1.00	2000
125	117	4	± 1.00	2000
125	115	5	± 1.00	2000
130	124	3	± 1.20	2000
130	122	4	± 1.20	2000
130	120	5	± 1.20	2000
133	127	3	± 1.20	2000
133	125	4	± 1.20	2000

133	123	5	± 1.20	2000
140	134	3	± 1.20	2000
140	132	4	± 1.20	2000
140	130	5	± 1.20	2000
150	144	3	± 1.20	2000
150	142	4	± 1.20	2000
150	140	5	± 1.20	2000
160	154	3	± 1.50	2000
160	152	4	± 1.50	2000
160	150	5	± 1.50	2000
170	164	3	± 1.50	2000
170	162	4	± 1.50	2000
170	160	5	± 1.50	2000
180	174	3	± 1.80	2000
180	172	4	± 1.80	2000
180	170	5	± 1.80	2000
185	179	3	± 1.85	2000
185	177	4	± 1.85	2000
185	175	5	± 1.85	2000
200	194	3	± 2.00	2000
200	192	4	± 2.00	2000
200	190	5	± 2.00	2000
230	222	4	± 2.30	2000
230	220	5	± 2.30	2000
250	242	4	± 2.50	2000
250	240	5	± 2.50	2000

Extruded Acrylic Tube Features

- Extruded Acrylic Tube is excellent weather resistance
- Excellent light transmission, light transmission rate of up to 92%, with crystal clear characteristics
- Machining is simple and convenient

Extruded Acrylic Tube Application

- Pack the container
- Industrial accessories
- Installation of artwork

Extruded Acrylic Tube Attention

- Do not coexist Extruded Acrylic Tube with other organic solvents, let alone expose them to organic solvents.
- Cannot be used at temperatures above 85 degrees Celsius.