

## 押出 PC 圓管規格

外徑 (mm)	內徑 (mm)	厚度 (mm)	外徑公差	長度 (mm)
5	3	1	± 0.15	2000
6	4	1	± 0.15	2000
7	5	1	± 0.15	2000
8	6	1	± 0.15	2000
8	5	1.5	± 0.15	2000
10	8	1	± 0.20	2000
10	7	1.5	± 0.20	2000
10	6	2	± 0.20	2000
12	10	1	± 0.20	2000
12	8	2	± 0.20	2000
12	6	3	± 0.20	2000
13	9	2	± 0.20	2000
13	7	3	± 0.20	2000
14	10	2	± 0.20	2000
14	8	3	± 0.20	2000
15	13	1	± 0.20	2000
15	11	2	± 0.20	2000
15	9	3	± 0.20	2000
16	12	2	± 0.30	2000
16	10	3	± 0.30	2000
18	14	2	± 0.30	2000
18	12	3	± 0.30	2000
20	18	1	± 0.30	2000

押出 PC 圓管規格

外徑 (mm)	內徑 (mm)	厚度 (mm)	外徑公差	長度 (mm)
20	16	2	± 0.30	2000
20	14	3	± 0.30	2000
22	18	2	± 0.30	2000
22	16	3	± 0.30	2000
25	21	2	± 0.40	2000
25	19	3	± 0.40	2000
28	24	2	± 0.40	2000
28	22	3	± 0.40	2000
30	26	2	± 0.40	2000
30	24	3	± 0.40	2000
30	22	4	± 0.40	2000
30	20	5	± 0.40	2000
32	28	2	± 0.40	2000
32	26	3	± 0.40	2000
32	24	4	± 0.40	2000
35	31	2	± 0.40	2000
35	29	3	± 0.40	2000
38	34	2	± 0.40	2000
38	32	3	± 0.40	2000
38	30	4	± 0.40	2000
38	28	5	± 0.40	2000
40	36	2	± 0.40	2000
40	34	3	± 0.40	2000

押出 PC 圓管規格

外徑 (mm)	內徑 (mm)	厚度 (mm)	外徑公差	長度 (mm)
40	32	4	± 0.40	2000
40	30	5	± 0.40	2000
45	41	2	± 0.40	2000
45	39	3	± 0.40	2000
45	37	4	± 0.40	2000
45	35	5	± 0.40	2000
50	46	2	± 0.40	2000
50	44	3	± 0.40	2000
50	42	4	± 0.40	2000
50	40	5	± 0.40	2000
60	56	2	± 0.40	2000
60	54	3	± 0.40	2000
60	52	4	± 0.40	2000
60	50	5	± 0.40	2000
70	66	2	± 0.60	2000
70	64	3	± 0.60	2000
70	62	4	± 0.60	2000
70	60	5	± 0.60	2000
80	76	2	± 0.60	2000
80	74	3	± 0.60	2000
80	72	4	± 0.60	2000
80	70	5	± 0.60	2000
90	86	2	± 0.60	2000

押出 PC 圓管規格

外徑 (mm)	內徑 (mm)	厚度 (mm)	外徑公差	長度 (mm)
90	84	3	± 0.60	2000
90	82	4	± 0.60	2000
90	80	5	± 0.60	2000
100	96	2	± 0.80	2000
100	94	3	± 0.80	2000
100	92	4	± 0.80	2000
100	90	5	± 0.80	2000
110	104	3	± 1.00	2000
110	102	4	± 1.00	2000
110	100	5	± 1.00	2000
120	114	3	± 1.00	2000
120	112	4	± 1.00	2000
120	110	5	± 1.00	2000
125	119	3	± 1.00	2000
125	117	4	± 1.00	2000
125	115	5	± 1.00	2000
130	124	3	± 1.20	2000
130	122	4	± 1.20	2000
130	120	5	± 1.20	2000
133	127	3	± 1.20	2000
133	125	4	± 1.20	2000
133	123	5	± 1.20	2000
140	134	3	± 1.20	2000

押出 PC 圓管規格

外徑 (mm)	內徑 (mm)	厚度 (mm)	外徑公差	長度 (mm)
140	132	4	± 1.20	2000
140	130	5	± 1.20	2000
150	144	3	± 1.20	2000
150	142	4	± 1.20	2000
150	140	5	± 1.20	2000
160	154	3	± 1.50	2000
160	152	4	± 1.50	2000
160	150	5	± 1.50	2000
170	164	3	± 1.50	2000
170	162	4	± 1.50	2000
170	160	5	± 1.50	2000
180	174	3	± 1.80	2000
180	172	4	± 1.80	2000
180	170	5	± 1.80	2000
185	179	3	± 1.85	2000
185	177	4	± 1.85	2000
185	175	5	± 1.85	2000
200	194	3	± 2.00	2000
200	192	4	± 2.00	2000
200	190	5	± 2.00	2000

## 押出PC圓管特色

- 耐衝擊/撞擊
- 耐熱性

## 押出PC圓管應用

- 透明包裝容器
- 工業配件
- 防爆燈管
- 公車站指示牌

## 押出PC圓管規格-客製化

- 以上為星銘押出PC圓管規格品規格，如果需要押出PC圓管特殊規格，歡迎與我們聯絡。

星銘產品

[壓克力圓管](#) [壓克力圓棒](#) [壓克力板&厚板](#)

[壓克力配件](#) [壓克力導光條](#) [壓克力補強條&壓克力異型品](#)

[壓克力擴散板, 導光板, 反射片](#) [壓克力窗簾棒](#) [鑽石拋光機](#)