



Acrylic Specification

Thickness Tolerance Permission

Type	Q	L	P
Length	1220mm	1220mm	2000mm
Width	1830mm	2440mm	3000mm
Thickness (mm)	Weight (KG)		
1.8	4.78	6.38	-
2.0	5.31	7.08	-
2.5	6.64	8.86	-
2.7	7.17	9.56	-
2.8	7.44	9.92	-
3.0	7.97	10.63	21.42
3.5	9.30	12.40	24.99
3.7	9.83	13.11	26.42
3.8	10.10	13.46	27.13
4.0	10.63	14.17	28.56
4.5	11.96	15.94	32.13
4.8	12.75	17.00	34.27
5.0	13.28	17.71	35.70
5.5	14.61	19.48	39.27
5.8	15.41	20.55	41.41
6.0	15.94	21.25	42.84
7.0	18.60	24.80	49.98
8.0	21.25	28.34	57.12
9.0	23.91	31.88	64.26
10.0	26.57	35.42	71.40
12.0	31.88	42.51	85.68
15.0	39.85	53.14	-
18.0	47.82	63.76	-
19.0	50.48	67.31	-
20.0	53.14	70.85	-
22.0	58.45	77.93	-
24.0	63.76	85.02	-
25.0	66.42	88.56	-
30.0	79.70	106.27	-
40.0	106.27	141.70	-
45.0	119.56	159.41	-
50.0	132.84	177.12	-

Type	Q、L	P
Thickness (mm)	Thickness Tolerance (%)	
1.8	15	-
2.0	12	-
2.5	10	-
2.8	10	-
3.0	10	17
3.5	10	17
3.7	10	17
3.8	10	17
4.0	8	14
4.5	8	14
4.8	8	14
5.0	8	14
5.5	8	14
5.8	8	14
6.0	6	12
7.0	6	12
8.0	5	10
9.0	5	10
10.0	4	8
12.0	4	8
15.0	4	8
18.0	4	8
19.0	4	8
20.0	4	8
22.0	4	8
24.0	4	8
25.0	4	8
30.0	4	8
40.0	4	8
45.0	4	8
50.0	4	8